

Subdivision of Section 23, T. 26 S. R. 2 W.,
Willamette Meridian, Oregon

CHAINS	
4.00	Abandoned dirt road, 15 lks. wide, bears N. 60° W. and S. 40° E.
5.45	Spur, slopes N. 10° W.; desc. 145 ft. over NW. slope.
6.80	Same dirt road, bears N. 50° E. and S. 15° W., in curve.
9.40	Enter heavy timber, edge bears N. 15° E. and S. 15° W.
14.75	Bottom of descent, slopes N. 30° W.; asc. 5 ft. along broken N. slope.
19.90	Creek, 3 lks. wide, course N. 15° E.; asc. 110 ft. over NE. slope.
24.60	Spur, slopes N. 60° E.; desc. 80 ft. along N. slope.
28.35	Creek, 2 lks. wide, course N. 20° W.; desc. 75 ft. along broken N. slope.
34.50	Creek, 4 lks. wide, course N. 30° W.; asc. 20 ft. along N. slope.
35.80	Creek, 1 lk. wide, course N. 20° E.; asc. 70 ft. along N. slope.
40.45	The center $\frac{1}{2}$ sec. cor. of sec. 23. Ascend 20 ft. along broken N. slope.
42.75	Spur, slopes N.; desc. 85 ft. over NW. slope.
51.40	Bottom of descent, slopes N.; asc. 40 ft. along N. slope.
56.20	Spur, slopes N. 40° W.; desc. 85 ft. over NW. slope.
60.25	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 23. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{W } \frac{1}{16} \\ \text{C} \quad \text{S } 23 \quad \text{C} \\ 1975 \end{array}$ </div>
	from which <div style="text-align: center;"> <p>A white fir, 12 ins. diam., bears N. 87$\frac{1}{2}$° E., 41$\frac{1}{2}$ lks. dist., mkd. CW $\frac{1}{16}$ S23 BT.</p> <p>A white fir, 8 ins. diam., bears S. 26° E., 26 lks. dist., mkd. CW $\frac{1}{16}$ S23 BT.</p> </div>
	Descend 40 ft. over NW. slope.
61.25	Ravine, drains N. 20° W.; asc. 25 ft. over NE. slope.
63.60	Spur, slopes N. 20° W.; desc. 350 ft. over broken NW. slope.
77.40	Creek, 4 lks. wide, course N. 25° W.; asc. 35 ft. over NE. slope.
80.05	The $\frac{1}{2}$ sec. cor. of sec. 23 only.

From the center W $\frac{1}{16}$ sec. cor. of sec. 23.