

15729

Subdivision of Section 23, T. 26 S., R. 2 W.,
Willamette Meridian, Oregon

CHAINS	
	N. 0° 21' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 23.
	Descend 375 ft. over NW. slope.
22.57	Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NW $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW 1/16 S 23 1975
	from which
	A cedar, 17 ins. diam., bears N. 6 $\frac{1}{2}$ ° E., 66 lks. dist., mkd. NW 1/16 S23 BT.
	A hemlock, 19 ins. diam., bears S. 26 $\frac{1}{2}$ ° W., 74 lks. dist., mkd. NW 1/16 S23 BT.
	Descend 95 ft. over N. slope.
25.25	Left bank of North Umpqua River, course S. 85° W.
28.80	Right bank of North Umpqua River, course S. 85° W.; asc. 20 ft. over SE. slope.
38.40	State Highway No. 138, 60 lks. wide, bears N. 75° E. and S. 75° W.
40.95	Susan Creek, 30 lks. wide, course S. 30° W.; asc. 10 ft. over nearly level land.
45.14	The W 1/16 sec. cor. of secs. 14 and 23.
	From the center N 1/16 sec. cor. of sec. 23.
	S. 87° 58' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 23.
	Ascend 50 ft. along broken N. slope.
19.83	The NW 1/16 sec. cor. of sec. 23.
	Descend 45 ft. along N. slope.
33.30	Bottom of descent, slopes N.; asc. 35 ft. along N. slope.
39.66	The N 1/16 sec. cor. of sec. 23 only.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>That portion of township 26 south, range 2 west, covered in this survey and resurvey, is situated approximately 10 miles southeasterly from the small town of Glide, Oregon. The area is drained by the North Umpqua River and various small streams flowing into it.</p> <p>Access into the area is by way of State Highway Number 138, extending along the river. Elevations in the area range from about 900 feet above sea level along the river bottoms to about 2,400 feet above sea level near the $\frac{1}{4}$ section corner of sections 23 and 26.</p>