

15733

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 31 S R 7 W
S 22 | S 23
S 27 | S 26
1964

from which the remains of the original bearing trees

A root hole, bears N. 36° E., 21 lks. dist., with a down fir alongside, 8 ins. diam., with healed blaze.

A root hole, bears S. 48° E., 25 lks. dist., with a down double trunked fir alongside, 25 ins. diam., with healed blaze.

A root hole, bears S. 14° W., 29 lks. dist., with a down fir alongside, 12 ins. diam., with decayed blaze.

A fir, 25 ins. diam., bears N. 68° W., 33 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Howard W. Johnstone, RLS No. 498, in 1962

A root hole, bears N. 10½° E., 17 lks. dist., with a down fir alongside, 13 ins. diam., with scribe marks T31S R7W S23 BT visible on open double blaze.

A fir, 13 ins. diam., bears S. 9½° E., 75 lks. dist., with healed double blaze.

A fir, 22 ins. diam., bears S. 14° W., 37 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 11 ins. diam., bears N. 2½° W., 118 lks. dist., mkd. T31S R7W S22 BT.

N. 0° 36' W., bet. secs. 22 and 23, marking and blazing the true line.

Ascend 105 ft. over SE. slope, through moderate timber and undergrowth.

17.50 Ravine, drains SE.; asc. 390 ft. over SE. slope.

20.35 New Stag Trail Road, gravelled, 30 lks. wide, bears N. 20° E. and S. 70° W., in curve.

28.55 Old Stag Trail Road, dirt, 20 lks. wide, bears N. 30° E. and S. 50° W., in curve, also ridge, bears same as road; desc. 105 ft. over NE. slope.

39.79 Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 7 W
¼
S 22 | S 23
1974