

15735

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 35 ins. diam., bears S. 80° E., 25 lks. dist., with fragmentary scribe marks visible on burned blaze.

A fir, 17 ins. diam., bears S. 27° W., 103 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Jelley

A fir stump, 30 ins. diam., bears N. 36½° E., 104 lks. dist., with scribe marks BT visible on open blaze.

A fir, 20 ins. diam., bears N. 83½° W., 118 lks. dist., with healed blaze.

and a new bearing tree

A fir, 27 ins. diam., bears N. 53° E., 229 lks. dist., mkd. T31S R7W S13 BT.

S. 89° 43' W., bet. secs. 14 and 23.

Ascend 135 ft. over NE. slope, through moderate timber and undergrowth.

4.30 Ridge, bears NW. and SE.; desc. 350 ft. over W. slope.

14.10 Ravine, drains S. 75° W.; desc. 190 ft. over SW. slope.

22.60 Spur, slopes SW.; desc. 450 ft. over SW. slope.

35.50 Creek, 3 lks. wide, course S. 60° W.; asc. 50 ft. over SE. slope.

36.90 Spur, slopes S.; desc. 40 ft. over SW. slope.

39.93 Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 7 W

¼ S 14
S 23

1974

from which

A fir, 10 ins. diam., bears N. 16½° W., 13½ lks. dist., mkd. ¼ S14 BT.

A fir, 8 ins. diam., bears S. 28° E., 17 lks. dist., mkd. ¼ S23 BT.

Descend 100 ft. over SW. slope.

47.50 Creek, 4 lks. wide, course S. 65° W.; asc. 50 ft. over E. slope.

50.80 Spur, slopes S.; desc. 160 ft. over SW. slope.

55.50 Creek, 1 lk. wide, course S. 20° E.; desc. 125 ft. over SW. slope.