

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| 3.80 | Spur, slopes E.; desc. 15 ft. over NE. slope. |
| 4.45 | Creek, 2 lks. wide, course S. 85° E.; asc. 25 ft. over SE. slope. |
| 7.65 | Top of ascent, slopes E.; desc. 140 ft. over NE. slope. |
| 15.85 | Creek, 2 lks. wide, course S. 85° E.; continue descent 150 ft. over NE. slope. |
| 22.50 | Creek, 3 lks. wide, course S. 65° E.; asc. 210 ft. over broken S. slope. |
| 33.35 | Spur, slopes N. 80° E.; desc. 235 ft. over NE. slope. |
| 41.08 | Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 31 S R 7 W $\frac{1}{4}$ S 10 S 11 1974 |
| | from which |
| | A fir, 9 ins. diam., bears N. 33 $\frac{1}{2}$ ° E., 37 lks. dist., mkd. $\frac{1}{4}$ S11 BT. |
| | A fir, 10 ins. diam., bears N. 6° W., 81 lks. dist., mkd. $\frac{1}{4}$ S10 BT. |
| | Descend 60 ft. over NE. slope. |
| 42.15 | Creek, 3 lks. wide, course N. 70° E.; asc. 265 ft. over SE. slope. |
| 53.45 | Spur, slopes NE.; desc. 475 ft. over NW. slope. |
| 72.00 | Creek, 2 lks. wide, course N. 30° E.; asc. 70 ft. over SE. slope. |
| 79.50 | Top of ascent, slopes E.; desc. 40 ft. over NE. slope. |
| 81.10 | Ravine, drains N. 50° E.; desc. 80 ft. over NE. slope. |
| 84.12 | Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original corner. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 31 S R 7 W S 3 S 2 S 10 S 11 1974 |
| | from which |
| | A fir, 18 ins. diam., bears N. 19° E., 18 lks. dist., mkd. T31S R7W S2 BT. |