

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

- CHAINS
34.00 Spur, slopes N. 15° W.; desc. 65 ft. over NW. slope.
- 39.50 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T 31 S R 7 W
 $\frac{1}{4}$ $\frac{S 15}{S 22}$
1974
- from which
- A fir, 13 ins. diam., bears N. 22° W., 52 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
- A fir, 26 ins. diam., bears S. 3 $\frac{1}{2}$ ° E., 9 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
- Descend 370 ft. over NW. slope.
- 47.60 Creek, 4 lks. wide, course N. 40° E.; asc. 375 ft. over NE. slope.
- 64.00 Spur, slopes N. 20° E.; desc. 35 ft. over gentle NW. slope.
- 71.20 Creek, 2 lks. wide, course N. 30° E.; asc. 85 ft. over NE. slope.
- 75.40 Spur, slopes N. 20° E.; desc. 50 ft. over NW. slope.
- 79.00 The cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S
S 16 | S 15 R
S 21 | S 22 7
1962 W

from which the remains of the original bearing trees

A fir, 18 ins. diam., bears N. 22° E., 49 lks. dist., with healed blaze. (Record, N. 18° E.)

A fir, 55 ins. diam., bears S. 69° E., 22 lks. dist., with healed blaze.

A cedar, 32 ins. diam., bears S. 58° W., 48 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 25° W., 9 lks. dist., with healed blaze.

and the remains of a bearing tree mkd. by Byron

A root hole, bears East, 6 lks. dist., with a down fir alongside, 5 ins. diam., with healed blaze.