

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 8 ins. diam., bears N. 15° E., 38 lks.
dist., mkd. T31S R7W S10 BT.

A fir, 8 ins. diam., bears S. 38½° E., 21 lks.
dist., mkd. T31S R7W S15 BT.

A fir, 10 ins. diam., bears S. 8° W., 33 lks.
dist., mkd. T31S R7W S16 BT.

A fir, 12 ins. diam., bears N. 12° W., 50 lks.
dist., mkd. T31S R7W S9 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, maple, pine, alder, oak,
madrone, chinquapin, and yew; undergrowth, vine maple,
hazel, arrowwood, salal, Oregon grape, and fern.

From the ¼ sec. cor. of secs. 10 and 15, perpetuated and
recorded by the Douglas County Surveyor, in 1970, monu-
mented with an iron post, 2 ins. diam., firmly set,
projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

¼ $\frac{S\ 10}{S\ 15}$

1970

from which the remains of the original bearing trees

A fir, 63 ins. diam., bears S. 45° W., 8 lks.
dist., with fragmentary scribe marks visible
on partially healed blaze; remarked CS BT by
the County Surveyor, in 1970.

and a bearing tree mkd. by the County Surveyor

A fir, 38 ins. diam., bears N. 59° W., 11 lks.
dist., with fragmentary scribe marks visible
on partially healed blaze.

N. 88° 05' W., bet. secs. 10 and 15.

Ascend 185 ft. over SE. slope, through moderate timber
and undergrowth.

5.65 Spur, slopes S.; desc. 60 ft. over SW. slope.

12.10 Ravine, drains S. 30° W.; asc. 145 ft. over SE. slope.

25.60 Ridge, bears N. 55° E. and S. 55° W.; desc. 365 ft.
over NW. slope.

39.65 The cor. of secs. 9, 10, 15, and 16.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, chinquapin, madrone, pine,
maple, and alder; undergrowth, vine maple, hazel, salal,
arrowwood, rhododendron, Oregon grape, poison oak, and
fern.

N. 0° 31' W., bet. secs. 9 and 10.