

15745

Dependent Resurvey, Portion of Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	COUNTY SURVEYORS OFFICE
	$\frac{1}{4} \frac{S 3}{S 10}$ T 31 S R 7 W 1974
	from which the original bearing trees A fir, 14 ins. diam., bears N. 60° E., 8 lks. dist., with illegible scribe marks visible on opened blaze. A fir, 25 ins. diam., bears S. 45° W., 17 lks. dist., with illegible scribe marks visible on opened blaze. and a bearing tree mkd. by the County Surveyor A fir, 15 ins. diam., bears S. 43° E., 28 lks. dist., with scribe marks $\frac{1}{4}$ S10 CS BT visible on open blaze.
	<hr/> N. 89° 50' W., beginning new measurement. Descend 230 ft. over NW. slope.
3.35	Creek, 3 lks. wide, course N. 40° W.; asc. 325 ft. over general E. slope.
19.80	Ridge, bears N. 30° E. and S. 20° W.; desc. 195 ft. over NW. slope.
24.70	Ravine, drains N. 45° W.; desc. 300 ft. over NW. slope.
40.60	The cor. of secs. 3, 4, 9, and 10. Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, madrone, chinquapin, pine, alder, and maple; undergrowth, vine maple, hazel, arrow-wood, huckleberry, salal, Oregon grape, rhododendron, and fern.
	From the cor. of secs. 9, 10, 15, and 16. N. 89° 07' W., bet. secs. 9 and 16. Descend 450 ft. over NW. slope, through moderate timber and undergrowth.
5.95	Gravelled road, 30 lks. wide, bears NE. and SW.
16.80	Head of ravine, drains N. 20° W.; desc. 10 ft. over NW. slope.
19.94	Point for the E 1/16 sec. cor. of secs. 9 and 16. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$E \frac{1}{16} \frac{S 9}{S 16}$ 1974
	from which