

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey executed by Dennis Hathorn,
U. S. Deputy Surveyor, in 1855,
and the resurvey by William H. Byars,
U. S. Deputy Surveyor, in 1882)

Beginning at the cor. of secs. 35 and 36 only, on the S.
bdy. of the Tp., determined at record bearing and distance
from the remains of the original bearing trees:

A saved fir stump, 33 ins. diam., bears S. $5\frac{1}{2}^{\circ}$ E.,
104 lks. dist., with scribe marks BT visible on
opened lower blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 29 S R 8 W
S 35 | S 36
T 30 S R 8 W S 1
1975

from which new bearing trees

A fir, 12 ins. diam., bears N. 20° E., 74 lks.
dist., mkd. T29S R8W S36 BT.

A fir, 9 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., 143 lks.
dist., mkd. T29S R8W S35 BT.

S. $89^{\circ} 25'$ W., along the S. bdy. of sec. 35, marking and
blazing the true line.

Descend 30 ft. over NW. slope, through clear cut area,
edge bears E. and W.

0.75 Ravine, drains N. 15° W.; asc. 10 ft. over NE. slope.

1.35 Top of ascent, slopes N.; desc. 70 ft. over SW. slope.

5.81 The cor. of secs. 1 and 2 only, T. 30 S., R. 8 W., per-
petuated and recorded by the County Surveyor, in 1967,
monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set,
projecting 12 ins. above ground, with brass cap mkd.

T 29 S
S 35
S 2 | S 1
T 30 S
R 8 W
1967

from which the remains of the original bearing trees

A root hole, bears N. 2° E., 30 lks. dist., with
a down fir alongside, 30 ins. diam., with
fragmentary scribe marks visible on bark blaze.

A saved fir stump, 30 ins. diam., bears S. 33° E.,
75 lks. dist., with fragmentary scribe marks
visible on bark blaze. (Record, S. 24° E.)

A cedar, 13 ins. diam., bears S. 67° W., 61 lks.
dist., with scribe marks BT visible on open
blaze. (Record, S. 59° W.)