

15751

355

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

	and the remains of a bearing tree mkd. by the County Surveyor
	A root hole, bears N. 84° E., 36 lks. dist., with a down fir alongside, 30 ins. diam., with fragmentary scribe marks visible on open blaze.
	Descend 5 ft. over SW. slope.
5.95	Ravine, drains N. 50° W.; asc. 35 ft. over NE. slope.
8.95	Spur, slopes N. 45° W.; desc. 160 ft. over NW. slope.
19.50	Ravine, drains N. 20° W.; asc. 55 ft. over NE. slope.
22.80	Spur, slopes N. 25° W.; desc. 80 ft. over NW. slope.
28.10	Creek, 2 lks. wide, course N.; asc. 15 ft. over NE. slope.
29.05	Spur, slopes N. 5° E.; desc. 40 ft. over NW. slope.
31.75	Bear Creek, 8 lks. wide, course N. 15° W.; asc. 205 ft. over SE. slope.
40.16	Point for the $\frac{1}{4}$ sec. cor. of sec. 35 only, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 S R 8 W $\frac{1}{4}$ S 35 T 30 S R 8 W 1975
	from which
	A fir, 5 ins. diam., bears N. 80 $\frac{1}{2}$ ° E., 28 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	A white fir, 8 ins. diam., bears N. 72° W., 25 lks. dist., mkd. $\frac{1}{4}$ S35 BT.
	Ascend 305 ft. over SE. slope.
59.45	Top of ascent, slopes S. 15° W.; desc. 110 ft. over SW. slope.
69.30	Ravine, drains S. 10° W.; asc. 35 ft. over SE. slope.
70.75	Spur, slopes S. 5° E.; desc. 35 ft. over SW. slope.
72.00	Ravine, drains S. 5° E.; asc. 80 ft. over SE. slope.
80.10	The cor. of secs. 34 and 35 only, on the S. bdy. of the Tp., perpetuated and recorded by the County Surveyor, in 1970, monumented with an iron post, 1 $\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	T 29 S R 8 W S 34 S 35 S 2 T 30 S 1970