

Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Byron

A fir, 26 ins. diam., bears S. 30° E., 64 lks. dist., with healed double blaze.

A fir, 20 ins. diam., bears S. 57° W., 68 lks. dist., with healed double blaze.

A fir, 16 ins. diam., bears N. 42° W., 89½ lks. dist., with healed double blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, alder, maple, madrone, pine, and yew; undergrowth, vine maple, poison oak, salal, hazel, ocean spray, blackberry, and huckleberry.

Dependant Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey executed by Dennis Hathorn,
U. S. Deputy Surveyor, in 1855,
and the resurvey by Fred Mensch,
Cadastral Engineer, in 1924)

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp.,

N. 0° 10' W., bet. secs. 35 and 36, marking and blazing the true line.

Descend 35 ft. over NW. slope, through heavy timber and moderate undergrowth.

1.60 Ravine, drains W.; desc. 320 ft. over NW. slope.

27.95 Gravelled road, 25 lks. wide, bears N. 45° E. and S. 45° W.

30.80 Bear Creek, 10 lks. wide, course N. 55° E.; asc. 90 ft. over SE. slope.

40.17 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼
S 35 | S 36
T 29 S R 8 W
1975

from which

A fir, 8 ins. diam., bears S. 73° E., 23½ lks. dist., mkd. ¼ S36 BT.

A fir, 14 ins. diam., bears S. 65¼° W., 25½ lks. dist., mkd. ¼ S35 BT.

Ascend 40 ft. over SE. slope.