

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

| CHAINS | <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, maple, oak, madrone, myrtle, chin- quapin, cedar, and alder; undergrowth, salal, poison oak, vine maple, Oregon grape, and fern.</p> |
|--------|--|
| | <p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$ 1924</p> |
| | <p>from which the remains of the original bearing trees</p> |
| | <p>A fir snag, 32 ins. diam., bears S. 59° E., 12 lks. dist., no marks visible.</p> |
| | <p>A fir snag, 36 ins. diam., bears N. 28° W., 17 lks. dist., with scribe marks BT visible on bark.</p> |
| | <p>and the remains of bearing trees mkd. by Mensch</p> |
| | <p>A fir snag, 30 ins. diam., bears S. 53° W., 27 lks. dist., with scribe marks $\frac{1}{4}$ S 24 visible on opened blaze.</p> |
| | <p>A fir stump, 36 ins. diam., bears N. 73° W., 59 lks. dist., with scribe marks S 13 BT visible on open blaze.</p> |
| | <p>and bearing trees mkd. by John Powell, Deputy County Sur- veyor, in 1970</p> |
| | <p>A fir, 5 ins. diam., bears S. 88° E., 18 lks. dist., with scribe marks $\frac{1}{4}$ S24 CS BT visible on partially healed blaze.</p> |
| | <p>A fir, 8 ins. diam., bears S. 60° W., 27 lks. dist., with scribe marks $\frac{1}{4}$ S24 CS BT visible on partially healed blaze.</p> |
| | <p>A fir, 14 ins. diam., bears N. 83° W., 30 lks. dist., with scribe marks $\frac{1}{4}$ S13 CS BT visible on partially healed blaze.</p> |
| | <p>N. 89° 43' W., bet. secs. 13 and 24.</p> |
| | <p>Descend 218 ft. over NW. slope, through moderate timber and undergrowth.</p> |
| 8.90 | <p>Ravine, drains NW.; desc. 40 ft. over NW. slope.</p> |
| 13.35 | <p>Ravine, drains N.; desc. 65 ft. over NW. slope.</p> |
| 17.25 | <p>Creek, 1 lk. wide, course N. 80° W.; desc. 10 ft. over NW. slope.</p> |
| 20.00 | <p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 13 and 24.</p> |
| | <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> |