

15757

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

W 1/16  $\frac{S 13}{S 24}$   
1975

from which

A fir, 22 ins. diam., bears N. 26° E., 83 lks.  
dist., mkd. W 1/16 S13 BT.

A fir, 16 ins. diam., bears S. 71° E., 81 lks.  
dist., mkd. W 1/16 S24 BT.

Descend over nearly level land.

21.75 Bottom of descent, drains N.; asc. 300 ft. over SE.  
slope.

23.80 Gravelled road, 25 lks. wide, bears N. 20° E. and  
S. 20° W.

38.00 Spur, slopes S.; desc. 15 ft. over SW. slope.

40.00 The cor. of secs. 13, 14, 23, and 24, monumented with  
an iron post, 2 ins. diam., firmly set, projecting 6 ins.  
above ground, with brass cap mkd.

T 29 S R 8 W  
 $\frac{S 14}{S 23} | \frac{S 13}{S 24}$   
1924

from which the remains of the original bearing trees

A madrone root crown, bears N. 33° E., 21 lks.  
dist.,

A root hole, bears S. 20° E., 16 lks. dist., with  
a down and decayed madrone alongside, 8 ins.  
diam., no marks visible.

A madrone snag, 8 ins. diam., bears N. 75° W., 11  
lks. dist., no marks visible on decayed blaze.

and bearing trees mkd. by Mensch

A cedar, 6 ins. diam., bears N. 40° E., 9 lks.  
dist., with scribe marks T29S R8W S13 BT visible  
on open blaze.

A fir, 38 ins. diam., bears S. 37° E., 48 lks.  
dist., with healed blaze.

A madrone, 8 ins. diam., bears S. 81° W., 46 lks.  
dist., no marks visible on decayed blaze.

A fir, 12 ins. diam., bears N. 7° W., 16 lks.  
dist., with healed blaze.

and a bearing tree mkd. by John Powell, Deputy County  
Surveyor, in 1966

A cedar, 8 ins. diam., bears S. 36½° W., 48 lks.  
dist., with scribe marks T29S R8W S23 CS BT  
visible on open blaze.

Land, mountainous.  
Soil, rocky clay loam.