

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>Timber, fir, cedar, madrone, alder, oak, and chinquapin; undergrowth, hazel, vine maple, arrowwood, salal, Oregon grape, poison oak, and huckleberry.</p>
	<p>North, bet. secs. 13 and 14.</p> <p>Ascend 110 ft. over S. slope, through moderate timber and undergrowth.</p>
4.50	Spur, slopes S. 35° E.; desc. 35 ft. over NE. slope.
9.60	Head of ravine, drains S. 70° E.; asc. 140 ft. over SE. slope.
16.85	Spur, slopes E.; desc. 35 ft. over NE. slope.
19.91	<p>Point for the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 14 S 13 1975</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 34° E., 5 lks. dist., mkd. S 1/16 S13 BT.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears S. 86° W., 54½ lks. dist., mkd. S 1/16 S14 BT.</p> <p>Descend 20 ft. over NE. slope.</p>
24.25	Head of ravine, drains S. 80° E.; asc. 170 ft. over SE. slope.
30.70	Ridge, bears N. 60° E. and S. 60° W.; desc. 305 ft. over NE. slope.
39.82	<p>The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 14 S 13 1924</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 12° W., 65 lks. dist., with scribe marks ¼ S visible on bark blaze.</p> <p>and the remains of bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A fir snag, 16 ins. diam., bears N. 89° E., 9 lks. dist., with scribe marks ¼ S visible on opened blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 34° W., 21 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by John M. Powell, Deputy County Surveyor, in 1966</p>