

15759

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears S. 55° E., 58 lks.
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, oak, chinquapin, and maple;
undergrowth, vine maple, hazel, salal, Oregon grape,
huckleberry, poison oak, and arrowwood.

From the cor. of secs. 12 and 13 only, on the E. bdy. of
the Tp., monumented with an iron post, 2 ins. diam.,
firmly set, projecting 6 ins. above ground, with brass
cap mkd.

T 29 S
S 12
S 13
R 8 W
1924

from which the remains of the original bearing trees

A root hole, bears N. 59° E., 39 lks. dist., with
a down black oak alongside, 20 ins. diam., no
marks visible.

A black oak, 40 ins. diam., bears S. 45° E., 77
lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Mensch

A root hole, bears S. 37° W., 62 lks. dist., with
a down black oak alongside, 14 ins. diam., no
marks visible on decayed blaze.

A black oak, 14 ins. diam., bears N. 5° W., 34
lks. dist., with partially healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County
Surveyor, in 1962

A pine, 24 ins. diam., bears S. 62° W., 16 lks.
dist., with fragmentary scribe marks visible
on partially healed blaze.

N. 89° 30' W., bet. secs. 12 and 13.

Descend 500 ft. over W. slope, through moderate timber
and undergrowth.

19.71 Point for the E 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, with brass cap mkd.

E 1/16 S 12
S 13
1975

from which

A fir, 26 ins. diam., bears N. 83° W., 15 lks.
dist., mkd. E 1/16 S12 BT.

A fir, 22 ins. diam., bears S. 19° W., 22 lks.
dist., mkd. E 1/16 S13 BT.