

Dependant Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	Descend 160 ft. over W. slope.
26.70	Dirt road, 15 lks. wide, bears N. and S.; thence over nearly level land.
28.20	Ravine, drains SE.
31.25	Ravine, drains SE.; asc. 150 ft. over SE. slope.
35.15	Gravelled road, 25 lks. wide, bears N. 15° W. and S. 30° W., in curve.
39.42	The $\frac{1}{2}$ sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	$\frac{S\ 12}{S\ 13}$ 1924
	from which the original bearing trees
	A white oak, 42 ins. diam., bears N. 30° E., 105 lks. dist., with healed blaze. (Record, 103 lks.)
	A white oak, 18 ins. diam., bears S. 64° E., 86 lks. dist., with scribe marks 4 S visible on opened blaze.
	and bearing trees mkd. by Mensch
	A white oak, 18 ins. diam., bears N. 11 $\frac{1}{2}$ ° E., 52 lks. dist., with healed blaze.
	A white oak, 22 ins. diam., bears S. 83° E., 37 lks. dist., with fragmentary scribe marks visible on partially healed blaze, as rescribed by John M. Powell, County Surveyor, in 1966.
	Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, pine, oak, madrone, chinquapin, and maple; undergrowth, fern, salal, Oregon grape, poison oak, huckleberry, and arrowwood.
	From the cor. of secs. 34 and 35 only, on the S. bdy. of the Tp.
	N. 0° 07' W., bet. secs. 34 and 35.
	Ascend 85 ft. over S. slope, through heavy timber and moderate undergrowth.
3.50	Ridge, bears N. 80° E. and S. 80° W.; desc. 360 ft. over NW. slope.
16.10	Creek, 2 lks. wide, course S. 80° W.; asc. 50 ft. over broken SW. slope.
18.75	Spur, slopes N. 75° W.; desc. 25 ft. over NW. slope.
20.05	Ravine, drains S. 55° W.; asc. 190 ft. over SW. slope.
36.70	Ridge, bears N. 40° W. and S. 45° E.; desc. 65 ft. over NE. slope.