

15763

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 22, 23, 26, and 27, perpetuated and recorded by the County Surveyor, in 1958, monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S R 8 W
S 22 | S 23
S 27 | S 26
1958

from which the remains of the original bearing trees

A decayed cedar snag, 26 ins. diam., bears S. 47° E., 33 lks. dist., with fragmentary scribe marks visible on open blaze.

A sawed fir stump, 40 ins. diam., bears S. 89° W., 50 lks. dist., with healed blaze.

and bearing trees mkd. by the County Surveyor

A fir, 9 ins. diam., bears N. 80° E., 6 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 25½° E., 40½ lks. dist., with healed blaze.

A chinquapin, 11 ins. diam., bears S. 72½° W., 29 lks. dist., with scribe marks 9 S R8W S2 visible on open blaze.

A chinquapin, 8 ins. diam., bears N. 2° W., 41 lks. dist., with scribe marks R8W S22 CS visible on open blaze.

N. 0° 13' E., bet. secs. 22 and 23.

Ascend 130 ft. over SW. slope, through scattering timber and moderate undergrowth.

- 1.25 Dirt road, 15 lks. wide, bears N. 65° W., curving N., and S. 50° E., curving S.
- 3.85 Spur, slopes S. 75° W.; desc. 85 ft. over broken NW. slope.
- 11.95 Same dirt road, 15 lks. wide, bears N. 45° E., curving N., and S. 45° W., curving S.
- 12.55 Ravine, drains N. 70° W.; asc. 10 ft. over NE. slope.
- 14.50 Spur, slopes N. 80° W.; desc. 65 ft. over NW. slope.
- 20.5 Ravine, drains W.; asc. 15 ft. over SW. slope.
- 21.65 Spur, slopes W.; desc. 55 ft. over NW. slope.
- 30.40 Bottom of descent, slopes S. 80° W.; asc. 15 ft. over SW. slope.
- 33.05 Spur, slopes S. 80° W.; desc. 25 ft. over NW. slope.
- 36.45 Creek, 1 lk. wide, course S. 75° W.; asc. 35 ft. over SW. slope.
- 36.55 Same dirt road, 15 lks. wide, bears N. 45° W., curving W., and S. 45° E., curving S.