

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS
40.16

Point for the $\frac{1}{2}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{2}$
S 22 | S 23
T 29 S R 8 W
1975

from which

A white fir, 13 ins. diam., bears S. 39° E., $33\frac{1}{2}$ lks. dist., mkd. $\frac{1}{2}$ S23 BT.

A white fir, 13 ins. diam., bears N. $53\frac{1}{2}^\circ$ W., $21\frac{1}{2}$ lks. dist., mkd. $\frac{1}{2}$ S22 BT.

Ascend 10 ft. over SW. slope.

44.15 Spur, slopes S. 70° W.; desc. 20 ft. over NW. slope.

46.70 Ravine, drains S. 85° W.; asc. 5 ft. over SW. slope.

48.20 Spur, slopes S. 80° W.; desc. 60 ft. over NW. slope.

51.75 Creek, 6 lks. wide, course W.; asc. 155 ft. over broken S. slope.

61.45 Spur, slopes S. 80° W.; desc. 110 ft. over NW. slope.

70.40 Ravine, drains N. 70° W.; asc. 15 ft. over SW. slope.

73.25 Spur, slopes S. 50° W.; desc. 65 ft. over NW. slope.

77.25 Ravine, drains N. 80° W.; asc. 20 ft. over SW. slope.

79.25 Spur, slopes W.; desc. 5 ft. over NW. slope.

80.32 Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 8 W
S 15 | S 14
S 22 | S 23
1975

from which

A fir, 6 ins. diam., bears N. $72\frac{1}{2}^\circ$ E., $46\frac{1}{2}$ lks. dist., mkd. T29S R8W S14 BT.

A fir, 4 ins. diam., bears S. $50\frac{1}{2}^\circ$ E., 21 lks. dist., mkd. X BT.

A white fir, 10 ins. diam., bears S. 50° W., 27 lks. dist., mkd. T29S R8W S22 BT.

A white fir, 10 ins. diam., bears N. $81\frac{1}{2}^\circ$ W., $27\frac{1}{2}$ lks. dist., mkd. T29S R8W S15 BT.