

15773

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS  
6.75

Middle Fork Coquille River, 25 lks. wide, course  
S. 32° E.; asc. 15 ft. over S. slope.

13.60

Bar Creek, 5 lks. wide, course S. 60° W.; asc. 60 ft.  
over S. slope.

40.11

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, perpetuated and record-  
ed by James W. Byron, Deputy County Surveyor, in 1962,  
from original evidence no longer in existence, monumented  
with an iron rod,  $\frac{3}{4}$  in. diam., with top 8 ins. below  
surface of ground.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 30 ins.  
in the ground, directly over iron rod, with top 2 ins.  
below surface and brass cap mkd.

*FD OK  
M. Smalley  
8/95 M 114-09*

T 29 S R 8 W  
 $\frac{1}{4}$   
S 7 | S 8  
1973

from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24  
ins. in the ground, for a reference monument,  
bears N. 42 $\frac{1}{2}$ ° E., 48 lks. dist., with brass cap  
mkd. T29S R8W S8 RM 1973 and an arrow pointing  
to the corner.

From this corner, a point established by Byron for a  
witness corner, bears East, 0.30 chs. dist., monumented  
with an iron post, 1 in. diam., firmly set, projecting  
8 ins. above ground, with brass cap mkd. COUNTY SURVEYORS  
OFFICE T29S R8W WC 21 Feet West to  $\frac{1}{4}$  S7 S8 1962, from  
which bearing trees mkd. by Byron:

A fir, 28 ins. diam., bears S. 48° E., 14 lks.  
dist., with healed double blaze.

An oak, 35 ins. diam., bears S. 35° W., 145 lks.  
dist., with scribe marks WC  $\frac{1}{4}$  S7 CS visible on  
partially healed double blaze.

Land, level.

Soil, sandy loam.

Timber, fir, hemlock, white fir, cedar, oak, alder, maple,  
madrone, pine, and yew; undergrowth, vine maple, poison  
oak, salal, hazel, ocean spray, fern, and blackberry.

From the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7, perpetuated and  
recorded by Milo E. Godfrey, Deputy County Surveyor, in  
1963, from original evidence no longer in existence,  
monumented with an iron pipe, 1 in. diam., firmly set,  
projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 29 S  
 $\frac{1}{4}$   $\frac{S 6}{S 7}$  R 8 W  
1963

from which bearing trees mkd. by Godfrey