

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir snag, 12 ins. diam., bears N. 27° W., 37½ lks. dist., with healed double blaze.</p> <p>A fir, 20 ins. diam., bears S. 16° W., 44 lks. dist., with healed double blaze.</p> <p>and a bearing tree of no record</p> <p>A yew, 28 ins. diam., bears N. 3° W., 14 lks. dist., with scribe marks ½ S6 BT visible on partially healed blaze.</p> <p>S. 88° 34' W., bet. secs. 6 and 7.</p> <p>Ascend 40 ft. over E. slope, through heavy timber and moderate undergrowth.</p>
1.60	Baldwin Road, paved, 40 lks. wide, bears N. 53° E. and S. 65° W., in curve.
9.15	Upper Camas Road, paved, 40 lks. wide, bears N. 30° W. and S. 10° E., in curve.
10.50	Top of ascent, slopes S.; desc. 20 ft. over SW. slope.
20.06	Point for the W 1/16 sec. cor. of secs. 6 and 7.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 6}{S\ 7}$ 1973</p> <p>from which</p> <p>A fir, 13 ins. diam., bears N. 55½° W., 19½ lks. dist., mkd. W 1/16 S6 BT.</p> <p>A fir, 23 ins. diam., bears S. 7½° E., 55½ lks. dist., mkd. W 1/16 S7 BT.</p> <p>Descend 15 ft. over SW. slope.</p>
24.50	Lang Creek, 4 lks. wide, course SE.; asc. 215 ft. over NE. slope.
41.40	Spur, slopes N. 65° W.; desc. 10 ft. over NW. slope.
42.84	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.
	<p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, oak, alder, maple, madrone, pine, and yew; undergrowth, vine maple, poison oak, salal, hazel, ocean spray, huckleberry, and blackberry.</p>
	<p>Subdivision of Section 7, T. 29 S., R. 8 W., Willamette Meridian, Oregon</p>
	<p>From the ½ sec. cor. of secs. 7 and 18.</p> <p>N. 0° 07' W., on the N. and S. center line of sec. 7.</p>