

15775

Subdivision of Section 7, T. 29 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS	
	Descend 20 ft. along W. side of Upper Camas Road.
30.00	Leave Upper Camas Road, paved, bears NW. and S., in curve.
33.45	Middle Fork Coquille River, 25 lks. wide, course S. 85° E.; asc. 5 ft. over nearly level land.
39.99	Point for the center ¼ sec. cor. of sec. 7, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">C ¼ S 7 1973</p>
	from which
	<p style="text-align: center;">A fir, 19 ins. diam., bears N. 42½° E., 198 lks. dist., mkd. C ¼ S7 BT.</p>
	<p style="text-align: center;">A cedar, 8 ins. diam., bears N. 11½° W., 34 lks. dist., mkd. C ¼ S7 BT.</p>
	Ascend 5 ft. over nearly level land.
60.20	Point for the center N 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">C N 1/16 S 7 C 1973</p>
	from which
	<p style="text-align: center;">A white fir, 10 ins. diam., bears S. 47½° E., 59½ lks. dist., mkd. CN 1/16 S7 BT.</p>
	<p style="text-align: center;">A yew, 13 ins. diam., bears S. 75° W., 36½ lks. dist., mkd. CN 1/16 S7 BT.</p>
	Descend 10 ft. over nearly level land.
70.00	Middle Fork Coquille River, 25 lks. wide, course S. 10° W.; asc. 10 ft. over nearly level land.
80.41	The ¼ sec. cor. of secs. 6 and 7.
	From the ¼ sec. cor. of secs. 7 and 8.
	S. 88°.51' W., on the E. and W. center line of sec. 7.
	Descend 55 ft. over W. slope, across open field.
38.50	Gravelled driveway, 15 lks. wide, bears N. and S.
40.46	The center ¼ sec. cor. of sec. 7.
	Descend 5 ft. over NW. slope, enter moderate timber and light undergrowth, edge bears N. and S.
44.30	Middle Fork Coquille River, 25 lks. wide, course S. 17° W.; asc. 130 ft. over SE. slope.