

Subdivision of Section 7, T. 29 S., R. 8 W.,  
Willamette Meridian, Oregon

CHAINS 49.50	Upper Camas Road, paved, 40 lks. wide, bears N. 2° E. and S. 7° E., in curve.
50.70	Gravelled road, 30 lks. wide, bears N. 2° E. and S. 7° E., in curve.
60.40	Point for the center W 1/16 sec. cor. of sec. 7.  Set an iron post, 28 ins. long, 2½ ins. diam., the top 8 ins. below the surface of the ground, with brass cap mkd.  $\begin{array}{c} \text{W } 1/16 \\ \text{C} \\ \text{S } 7 \\ 1973 \end{array}$  from which  A fir, 6 ins. diam., bears N. 4½° E., 98 lks. dist., mkd. CW 1/16 S7 BT.  A fir, 15 ins. diam., bears S. 81½° W., 95 lks. dist., mkd. CW 1/16 S7 BT.  From this point, the SW. corner of George W. Smith's house, bears N. 29½° E., 171 lks. dist., the long side bears N. 73° E.  Corner is located on S. edge of gravelled driveway, 25 lks. wide, bears N. 80° E. and S. 80° W.  Ascend 35 ft. over SE. slope.
65.30	Top of ascent, slopes S.; desc. 80 ft. over SW. slope.
83.42	The ½ sec. cor. of secs. 7 and 12.
	From the center W 1/16 sec. cor. of sec. 7.  N. 0° 11' W., on the N. and S. center line of the NW¼.  Ascend 170 ft. over SE. slope.
7.45	Top of ascent, slopes E.; desc. 50 ft. over N. slope.
20.16	Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NW¼.  Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \text{NW } 1/16 \text{ S } 7 \\ 1973 \end{array}$  from which  A cedar, 8 ins. diam., bears N. 55½° E., 26 lks. dist., mkd. NW 1/16 S7 BT.  A white fir, 12 ins. diam., bears S. 85½° W., 48 lks. dist., mkd. NW 1/16 S7 BT.  Ascend 55 ft. over S. slope.
22.90	Dirt road, 20 lks. wide, bears N. 35° W. and S. 60° E., in curve.