

15777

Subdivision of Section 7, T. 29 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS 25.45	Spur, slopes E.; desc. 290 ft. over SE. slope.
35.70	Lang Creek, 5 lks. wide, course S. 24° E.; asc. 15 ft. over S. slope.
40.31	The W 1/16 sec. cor. of secs. 6 and 7.
	From the center N 1/16 sec. cor. of sec. 7. S. 88° 42' W., on the E. and W. center line of the NW¼. Descend 10 ft. over SW. slope.
1.50	Middle Fork Coquille River, 25 lks. wide, course S. 86° W.; asc. 295 ft. over SE. slope.
5.86	Upper Camas Road, paved, 40 lks. wide, bears S. 18° W. and N. 6° W., in curve.
11.95	Dirt road, 20 lks. wide, bears S. 24° E. and N. 38° W., in curve.
13.65	Spur, slopes S. 20° W.; desc. 45 ft. over W. slope.
19.99	The NW 1/16 sec. cor. of sec. 7. Descend 15 ft. over broken SW. slope.
42.88	The N 1/16 sec. cor. of secs. 7 and 12.
	Subdivision of Section 13, T. 29 S., R. 8 W., Willamette Meridian, Oregon
	From the ¼ sec. cor. of secs. 13 and 24. N. 0° 01' W., on the N. and S. center line of sec. 13. Descend 140 ft. over NW. slope, through heavy timber and dense undergrowth.
8.00	Creek, 1 lk. wide, course N. 70° W.; asc. 15 ft. over SW. slope.
10.90	Spur, slopes W.; desc. 105 ft. over NW. slope.
18.60	Ravine, drains N. 40° W.; asc. 5 ft. over SW. slope.
20.00	Point for the center S 1/16 sec. cor. of sec. 13. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	C S 1/16 S 13 C 1975
	from which A fir, 12 ins. diam., bears N. 15° E., 35 lks. dist., mkd. CS 1/16 S13 BT. A fir, 10 ins. diam., bears S. 80° W., 49 lks. dist., mkd. CS 1/16 S13 BT.