

Subdivision of Section 13, T. 29 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS	
	Corner is located on spur, slopes NW.
	Descend 45 ft. over NW. slope.
23.45	Ravine, drains N. 35° W.; asc. 25 ft. over SW. slope.
30.75	Top of ascent, slopes W.; desc. 90 ft. over NW. slope.
40.00	Point for the center $\frac{1}{2}$ sec. cor. of sec. 13, at inter- section with the E. and W. center line.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 29 S R 8 W C $\frac{1}{2}$ S 13 1975</p>
	from which
	A fir, 12 ins. diam., bears S. 25° W., 129 lks. dist., mkd. C $\frac{1}{2}$ S13 BT.
	A fir, 12 ins. diam., bears N. 15° W., 27 lks. dist., mkd. C $\frac{1}{2}$ S13 BT.
	Thence over nearly level land.
40.45	Wire fence, bears E. and W.
49.50	Creek, 5 lks. wide, course N. 15° W.
54.00	Berry Creek, 30 lks. wide, course N. 45° E.; asc. 190 ft. over SE. slope.
59.50	Wire fence, bears N. 45° E. and S. 45° W.
76.30	Gravelled road, 25 lks. wide, bears N. 45° E. and S. 45° W.
77.10	Wire fence, bears N. 45° E. and S. 45° W.
80.04	The $\frac{1}{2}$ sec. cor. of secs. 12 and 13.
	From the $\frac{1}{2}$ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">$\frac{1}{2}$ S 13 1924</p>
	from which the remains of the original bearing trees
	A fir stump, 30 ins. diam., bears N. 45° E., 28 lks. dist., with healed blaze.
	A root hole, bears N. 52° W., 30 lks. dist., with a down and decayed oak alongside, size indeter- minate, no marks visible.
	and the remains of bearing trees mkd. by Mensch
	A fir, 18 ins. diam., bears S. 52° W., 19 lks. dist., with healed blaze.