

15779

Subdivision of Section 13, T. 29 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>A fir stump, 8 ins. diam., bears N. 87° W., 41 lks. dist., with scribe marks BT visible on opened blaze.</p>
	<p>and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962</p>
	<p>A root hole, bears N. 87½° W., 24 lks. dist., with a down fir alongside, 10 ins. diam., with scribe marks ¼ S13 CS visible on open blaze.</p>
	<p>and a new bearing tree</p>
	<p>A fir, 10 ins. diam., bears N. 32° W., 23 lks. dist., mkd. ¼ S13 BT.</p>
	<p>N. 89° 58' W., on the E. and W. center line of sec. 13.</p>
	<p>Descend 70 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
4.25	<p>Berry Creek, 35 lks. wide, course S. 55° E.; asc. 130 ft. over NE. slope.</p>
19.75	<p>Point for the center E 1/16 sec. cor. of sec. 13.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{---} \text{S } 13 \text{---} \text{C} \\ 1975 \end{array}$ </p>
	<p>from which</p>
	<p>A fir, 10 ins. diam., bears N. 81° E., 27 lks. dist., mkd. CE 1/16 S13 BT.</p>
	<p>A fir, 8 ins. diam., bears S. 64° W., 28 lks. dist., mkd. CE 1/16 S13 BT.</p>
	<p>Ascend 75 ft. over NE. slope.</p>
24.45	<p>Spur, slopes N. 25° W., enter logged area, edges bear N. and W.; desc. 160 ft. over SW. slope.</p>
33.95	<p>Creek, 5 lks. wide, course N. 30° W.; thence over nearly level land.</p>
38.90	<p>Wire fence, bears N. and S.</p>
39.50	<p>The center ¼ sec. cor. of sec. 13.</p>
	<p>Continue over nearly level land.</p>
49.50	<p>Creek, 5 lks. wide, course N. 15° E.; continue over nearly level land.</p>
54.95	<p>Wire fence, bears N. and S.</p>
55.70	<p>Gravelled road, 25 lks. wide, bears N. and S.</p>
56.50	<p>Wire fence, bears N. and S.</p>
59.49	<p>Point for the center W 1/16 sec. cor. of sec. 13.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>