

Subdivision of Section 13, T. 29 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS	
	$\frac{W \ 1/16}{S \ 13} C$ 1975
	from which A fir, 6 ins. diam., bears S. 13° E., 18 lks. dist., mkd. CW 1/16 S13 BT. A fir, 20 ins. diam., bears N. 59° W., 40 lks. dist., mkd. CW 1/16 S13 BT. Ascend 260 ft. over NE. slope.
60.25	Gravelled road, 20 lks. wide, bears N. 70° W. and S. 70° E.
69.85	Spur, slopes N.; desc. 30 ft. over NW. slope.
73.25	Head of ravine, slopes N. 20° E.; asc. 205 ft. over NE. slope.
79.48	The ¼ sec. cor. of secs. 13 and 14.
	From the center E 1/16 sec. cor. of sec. 13. N. 0° 04' W., on the N. and S. center line of the NE¼. Descend 115 ft. over NE. slope, through scattered timber and undergrowth.
3.25	Berry Creek, 35 lks. wide, course S. 80° E.; asc. 185 ft. over SW. slope.
18.25	Spur, slopes S. 85° W.; desc. 60 ft. over NW. slope.
21.00	Creek, 1 lk. wide, course S. 80° W.; asc. 125 ft. over SW. slope.
32.00	Spur, slopes N. 60° W.; desc. 70 ft. over NW. slope.
35.35	Ravine, drains N. 80° W.; asc. 35 ft. over SW. slope.
39.88	The E 1/16 sec. cor. of secs. 12 and 13.
	From the W 1/16 sec. cor. of secs. 13 and 24. North, on the N. and S. center line of the SW¼. Over nearly level land, through moderate timber and undergrowth.
3.00	Creek, 5 lks. wide, course N. 15° E.; continue over nearly level land.
11.50	Gravelled road, 25 lks. wide, bears N. 20° E. and S. 20° W.; asc. 85 ft. over SE. slope.
19.95	Point for the SW 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	SW 1/16 S 13 1975