

15785

## T. 27 S., R. 4 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and subdivision of section 23, township 27 south, range 4 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The north boundary and a portion of the subdivisional lines were surveyed by Addison R. Flint, in 1855.

A portion of the subdivisional lines was resurveyed and the subdivision of the township was completed by Elmer F. Strickler, in 1917.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 31, 1974, for Group Number 855, Oregon.

The directions of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice to preclude error. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 23 and 26 only, as scaled from the Dixonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude 43° 12.0' N. Longitude 123° 07.6' W.

The mean magnetic declination is 20° 00' E.

Dependent Resurvey of a Portion of the North Boundary,  
T. 27 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey by Addison R. Flint,  
U. S. Deputy Surveyor, in 1855)

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., perpetuated and recorded by James W. Byron, County Surveyor, in 1964, monumented with an iron post, 2 ins. diam., protruding 12 ins. above ground, with brass cap mkd.

T 26 S R 4 W  
 $\frac{1}{4}$   $\frac{S 35}{S 2}$   
 T 27 S R 4 W  
 1964