

15788

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS									
	At the corner point								
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T 27 S R 4 W</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 23</td> <td style="padding-left: 5px;">S 24</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 26</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">1975</td> </tr> </table>	T 27 S R 4 W		S 23	S 24	S 26		1975	
T 27 S R 4 W									
S 23	S 24								
S 26									
1975									
	Deposit corner stone and reset iron rod alongside iron post.								
	Corner is located at fence corner, wire fences extend S. and W.								
	N. 0° 03' E., bet. secs. 23 and 24, marking and blazing the true line.								
	Descend 55 ft. over gradual NW. slope, through medium timber and undergrowth.								
6.40	Spur, slopes W.; desc. 130 ft. over N. slope.								
7.90	Lane Mountain Road, gravelled, 15 lks. wide, bears N. 84° W. and S. 70° E., in curve.								
11.45	Spur, slopes N. 10° W.; desc. 80 ft. over NE. slope.								
14.85	Creek, 5 lks. wide, course N. 82° W.; asc. 80 ft. over broken SW. slope.								
21.65	Rocky spur, slopes S. 52° W.; desc. 70 ft. over broken NW. slope.								
26.45	Ravine, drains N. 62° W.; asc. 20 ft. over SW. slope.								
29.65	Spur, slopes N. 74° W.; desc. 50 ft. over NW. slope.								
31.75	Ravine, drains N. 78° W.; asc. 35 ft. over SW. slope.								
36.60	Spur, slopes N. 70° W.; desc. 75 ft. over N. slope.								
39.59	From this point, the ¼ sec. cor. of sec. 24 only, bears West, 0.09 chs. dist., monumented with an iron post, 1½ ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">¼</td> <td style="padding-left: 5px;">S 24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1917</td> </tr> </table>	¼	S 24	1917					
¼	S 24								
1917									
	from which the remains of bearing trees mkd. by Strickler								
	A fir stump, 40 ins. diam., bears N. 67° E., 55 lks. dist., with healed blaze.								
	A fir, 60 ins. diam., bears S. 68° E., 33 lks. dist., with healed blaze. (Record, S. 73° E.)								
	and a bearing tree mkd. by James W. Byron, County Surveyor, in 1959								
	A fir, 34 ins. diam., bears S. 30° E., 61 lks. dist., with healed blaze.								