

15789

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	Descend 40 ft. over N. slope.
40.56	<p>The $\frac{1}{4}$ sec. cor. of sec. 23 only, perpetuated and recorded by James W. Byron, County Surveyor, in 1959, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, protruding 14 ins. above ground, from which the remains of the bearing trees mkd. by Strickler:</p>
	<p>A fir, 42 ins. diam., bears S. 60° W., 16 lks. dist., with scribe marks S 2 visible on opened blaze.</p>
	<p>A decayed fir stump, size indeterminate, bears N. 71° W., 60 lks. dist., no marks visible.</p>
	and a bearing tree mkd. by Byron
	<p>A fir, 22 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ W., 79 lks. dist., with fragmentary scribe marks visible on partially open blaze.</p>
	At the corner point
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 27 S R 4 W $\frac{1}{4}$ S 23 1975</p>
	Reset iron pipe alongside iron post.
	N. $0^{\circ} 18'$ E., beginning new measurement.
	Descend 130 ft. over N. slope.
2.45	Bottom of steep descent; desc. 15 ft. over gentle NW. slope.
3.65	Ravine, drains S. 64° W.; asc. 2 ft. over SW. slope.
4.40	Spur, slopes N. 70° W.; desc. 45 ft. across NW. slope.
7.40	Creek, 5 lks. wide, course N. 70° W.; asc. 100 ft. over SW. slope.
12.50	Spur, slopes N. 70° W.; desc. 120 ft. over NW. slope.
14.90	Creek, 7 lks. wide, course N. 70° W.; asc. 20 ft. over SW. slope.
15.80	Spur, slopes W.; desc. 10 ft. over NW. slope.
16.35	Ravine, drains W.; asc. 70 ft. over broken SW. slope.
20.215	Point for the N $\frac{1}{16}$ sec. cor. of sec. 23 only.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">N $\frac{1}{16}$ S 23 1975</p>
	from which