

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A cedar, 12 ins. diam., bears N. 66° W., 31 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Godfrey</p> <p>A cedar, 8 ins. diam., bears N. 71° E., 53 lks. dist., with scribe marks R4W SC visible on open blaze.</p> <p>The corner stone set by Strickler, in 1917, a hard limestone, 16 x 6 x 6 ins., was found alongside the iron post.</p> <p>N. 0° 10' W., bet. secs. 22 and 23.</p> <p>Descend 10 ft. over NW. slope, through moderate timber and undergrowth.</p>
1.10	Ravine, drains S. 80° W.; asc. 45 ft. over broken SW. slope.
5.90	Spur, slopes S. 56° W.; desc. 25 ft. over W. slope.
7.90	Ravine, drains S. 38° W.; asc. 15 ft. over SW. slope.
9.90	Spur, slopes S. 80° W.; desc. 95 ft. over broken NW. slope.
17.60	Ravine, drains W.; asc. 15 ft. over SW. slope.
19.45	Spur, slopes S. 50° W.; desc. 60 ft. over NW. slope.
25.80	Spur, slopes N. 64° W.; desc. 175 ft. over NE. slope.
34.20	Ravine, drains N. 38° W.; desc. 80 ft. over broken NE. slope.
40.09	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 S R 4 W $\frac{1}{4}$ S 22 S 23 1975</p> <p>from which</p> <p>A fir, 9 ins. diam., bears S. 20° E., 23 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>A fir, 8 ins. diam., bears N. 70° W., 30 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>From this point, a local corner established by James W. Byron, County Surveyor, in 1959, bears N. 1° 30' E., 0.29 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 22 S 23 T 27 S R 4 W 1959</p>