

15794

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS					
	<p>from which bearing trees mkd. by Byron</p> <p>A fir, 8 ins. diam., bears S. 73° E., 79 lks. dist., with healed blaze.</p> <p>A fir, 16 ins. diam., bears N. 46° W., 36 lks. dist., with healed blaze.</p> <p>Descend 270 ft. over NW. slope.</p>				
59.80	Spur, slopes N. 50° W.; desc. 105 ft. over NE. slope.				
64.40	Creek, 5 lks. wide, course N. 50° W.; asc. 90 ft. over SW. slope.				
69.25	Spur, slopes N. 72° W.; desc. 35 ft. over SW. slope.				
71.20	Ravine, drains W.; asc. 20 ft. over S. slope.				
75.00	Spur, slopes N. 71° W.; desc. 45 ft. over NE. slope.				
78.70	Creek, 8 lks. wide, course N. 68° W.; asc. 30 ft. over SW. slope.				
79.55	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E.				
80.18	<p>Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 27 S R 4 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p>1975</p> </div> <p>from which</p> <p>A cedar, 7 ins. diam., bears N. 40° E., 59 lks. dist., mkd. T27S R4W S14 BT.</p> <p>A cedar, 8 ins. diam., bears S. 40½° E., 23 lks. dist., mkd. T27S R4W S23 BT.</p> <p>A cedar, 10 ins. diam., bears S. 1° W., 52 lks. dist., mkd. T27S R4W S22 BT.</p> <p>A cedar, 6 ins. diam., bears N. 37° W., 133 lks. dist., mkd. T27S R4W S15 BT.</p> <p>From this point, the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., bears N. 0° 36' W., 241.25 chs. dist., hereinbefore described.</p> <p>This control line was fully retraced, and careful search was made for evidence of intervening corners, none of which was recovered.</p> <p>From this same point, the ¼ sec. cor. of secs. 15 and 22, bears N. 89° 17' W., 39.78 chs. dist., perpetuated and recorded by James W. Byron, County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, protruding 8 ins. above ground, from which bearing trees described by Byron:</p>	S 15	S 14	S 22	S 23
S 15	S 14				
S 22	S 23				