

15796

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS 7.85	Ridge, bears N. 80° W. and S. 80° E.; desc. 230 ft. over SW. slope.
19.975	<p>Point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	$\begin{array}{r} \text{E } 1/16 \quad \text{S } 14 \\ \quad \quad \quad \text{S } 23 \\ \quad \quad \quad 1975 \end{array}$
	<p>from which</p> <p>A fir, 10 ins. diam., bears N. 82° W., 59 lks. dist., mkd. E 1/16 S14 BT.</p> <p>A fir, 10 ins. diam., bears S. 6° W., 62 lks. dist., mkd. E 1/16 S23 BT.</p>
	<p>From this point, a local corner established by person(s) unknown, and subsequently perpetuated and recorded by James W. Byron, County Surveyor, in 1959, bears N. 3° 35' W., 0.24 chs. dist., monumented with an iron rod, ¾ in. diam., firmly set, protruding 4 ins. above ground, from which the remains of bearing trees not of record:</p>
	<p>A fir, 18 ins. diam., bears N. 20° E., 18 lks. dist., with scribe marks CS S14 visible on bark blaze.</p>
	<p>A cedar stump, 36 ins. diam., bears West, 61 lks. dist., with healed blaze.</p>
	<p>and the remains of a bearing tree mkd. by Byron</p>
	<p>A fir snag, 30 ins. diam., bears N. 43° W., 62 lks. dist., with illegible scribe marks visible on open blaze.</p>
	<p>Descend 340 ft. over SW. slope.</p>
33.60	<p>Ravine, drains S. 25° W.; asc. 5 ft. over SE. slope.</p>
38.10	<p>Spur, slopes S. 55° W.; desc. 15 ft. over SW. slope.</p>
39.95	<p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	$\begin{array}{r} \text{T } 27 \text{ S } \text{R } 4 \text{ W} \\ \quad \quad \quad \text{S } 14 \\ \quad \quad \quad \text{S } 23 \\ \quad \quad \quad 1975 \end{array}$
	<p>from which</p> <p>An oak, 10 ins. diam., bears N. 74° W., 46 lks. dist., mkd. ¼ S14 BT.</p> <p>An oak, 8 ins. diam., bears S. 42° W., 47 lks. dist., mkd. ¼ S23 BT.</p>