

15797

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, a local corner, established by James W. Byron, County Surveyor, in 1959, bears N. 10° 10' W., 0.29 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 27 S R 4 W ¼ $\frac{S 14}{S 23}$ 1959</p> <p>from which bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 1° 30' E., 62 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 83° W., 39 lks. dist., with healed blaze.</p> <p>Descend 240 ft. over SW. slope.</p>
49.10	Dirt road, 15 lks. wide, bears S. 20° E. and N. 20° W.
53.40	Deer Creek, 10 lks. wide, course N. 28° W.; asc. 105 ft. over NE. slope.
59.75	Enter open field, edge bears N. and S.
61.40	Ridge, bears N. and S.; desc. 170 ft. over SW. slope.
79.90	The cor. of secs. 14, 15, 22, and 23.
	<p>Land, mountainous, with rolling hills. Soil, rocky clay and loam. Timber, fir, cedar, pine, hemlock, oak, madrone, alder, and chinquapin; undergrowth, vine maple, arrowwood, salal, poison oak, manzanita, and hazel.</p>
	<p>Subdivision of Section 23, T. 27 S., R. 4 W., Willamette Meridian, Oregon</p>
	<p>From the ¼ sec. cor. of secs. 23 and 26.</p> <p>N. 0° 03' E., on the N. and S. center line of sec. 23.</p> <p>Descend 210 ft. over NE. slope, through moderate timber and undergrowth.</p>
21.85	Gravelled road, 15 lks. wide, bears N. 20° E. and S. 20° W.
32.75	Gravelled road, 15 lks. wide, bears N. 40° W. and S. 40° E.
34.20	Spur, slopes N. 50° W.; desc. 55 ft. over NE. slope.
36.82	Creek, 10 lks. wide, course N. 30° W.; asc. 10 ft. over SW. slope.
38.08	Spur, slopes N. 40° W.; desc. 60 ft. over NE. slope.
40.20	Point for the center ¼ sec. cor. of sec. 23, at intersection with the E. and W. center line.