

15798

Subdivision of Section 23, T. 27 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 27 S R 4 W C ¼ S 23 1975
	from which
	A fir, 45 ins. diam., bears N. 1° E., 126 lks. dist., mkd. C ¼ S23 BT.
	A maple, 7 ins. diam., bears S. 85° W., 59½ lks. dist., mkd. C ¼ S23 BT.
	Corner is located on a NE. slope, 38 lks. distance, west of center line of creek, at base of rock wall, approximately 15 ft. high.
	Descend 175 ft. over steep NW. slope.
55.10	Ravine, drains W.; asc. 2 ft. over SW. slope.
55.80	Spur, slopes W.; desc. 45 ft. over NE. slope.
58.05	Creek, 15 lks. wide, course N. 4° W.; desc. 5 ft. over NW. slope.
60.34	Point for the center N 1/16 sec. cor. of sec. 23.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	C N 1/16   S 23 C 1975
	from which
	A hemlock, 12 ins. diam., bears S. 20° E., 21 lks. dist., mkd. CN 1/16 S23 BT.
	A cedar, 11 ins. diam., bears S. 89½° W., 26 lks. dist., mkd. CN 1/16 S23 BT.
	Descend 35 ft. over NW. slope.
63.50	Ravine, drains N. 53° W.; asc. 40 ft. over SW. slope.
65.40	Spur, slopes W.; desc. 105 ft. over N. slope.
68.65	Deer Creek, 12 lks. wide, course W.; asc. 50 ft. over S. slope.
72.20	Gravelled road, 12 lks. wide, bears E. and W.
	Ascend 10 ft. over S. slope.
72.90	Spur, slopes S. 30° W.; desc. 2 ft. over NW. slope.
74.90	Ravine, drains S. 55° W.; asc. 95 ft. over S. slope.
80.48	The ¼ sec. cor. of secs. 14 and 23.
	From the ¼ sec. cor. of sec. 23 only.