

15799

Subdivision of Section 23, T. 27 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	S. 89° 40' W., on the E. and W. center line of sec. 23. Ascend 25 ft. across NE. slope, through moderate timber and undergrowth.
1.85	Spur, slopes N. 54° W.; desc. 225 ft. over SW. slope.
9.70	Creek, 6 lks. wide, course N. 45° W.; desc. 20 ft. over SW. slope.
11.90	Spur, slopes N.; desc. 55 ft. over NW. slope.
14.30	Deer Creek, 8 lks. wide, course N. 30° E.; asc. 125 ft. over NE. slope.
19.15	Ravine, drains N. 75° E.; asc. 20 ft. over SE. slope.
19.89	Point for the center E 1/16 sec. cor. of sec. 23. Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{S } 23 \quad \text{C} \\ 1975 \end{array}$ </div>
	from which <div style="text-align: center;"> <p>A fir, 8 ins. diam., bears N. 49° E., 6 lks. dist., mkd. CE 1/16 S23 BT.</p> <p>A fir, 8 ins. diam., bears S. 12° W., 26 lks. dist., mkd. CE 1/16 S23 BT.</p> </div>
	Ascend 135 ft. over broken SE. slope.
24.40	Ridge, bears N. 26° W. and S. 26° E.; desc. 95 ft. over SW. slope.
30.70	Ravine, drains N.; asc. 5 ft. over NE. slope.
34.40	Spur, slopes N. 20° W.; desc. 45 ft. over SW. slope.
36.55	Ravine, drains N. 75° W.; desc. 85 ft. over NW. slope.
39.78	The center ¼ sec. cor. of sec. 23. Ascend 110 ft. over NE. slope.
44.80	Gravelled road, 18 lks. wide, bears N. 10° W. and S. 10° E.
54.10	Spur, slopes N.; desc. 25 ft. over NW. slope.
56.90	Ravine, drains N. 15° E.; asc. 5 ft. over NE. slope.
57.95	Spur, slopes N. 13° W.; desc. 190 ft. over NW. slope.
69.20	Ravine, drains N. 10° W.; asc. 10 ft. over NE. slope.
70.55	Spur, slopes N. 20° W.; desc. 105 ft. over NW. slope.
77.35	Ravine, drains N.; asc. 50 ft. over NE. slope.
79.63	The ¼ sec. cor. of secs. 22 and 23.