

15800

Subdivision of Section 23, T. 27 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	N. 0° 09' E., along the N. and S. center line of the NE $\frac{1}{4}$ of sec. 23.
	Ascend 20 ft. over SE. slope, through moderate timber and undergrowth.
3.95	Spur, slopes E.; desc. 80 ft. over NE. slope.
8.20	Ravine, drains S. 81° E.; asc. 20 ft. over SE. slope.
10.90	Spur, slopes E.; desc. 197 ft. over NE. slope.
20.17	Point for the NE 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NE $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NE 1/16 S 23 1975
	from which
	A hemlock, 11 ins. diam., bears S. 55° E., 26 lks. dist., mkd. NE 1/16 S23 BT.
	A fir, 10 ins. diam., bears S. 1° E., 46 lks. dist., mkd. NE 1/16 S23 BT.
	Descend 90 ft. over NE. slope.
23.15	Deer Creek, 12 lks. wide, course N. 40° W.; asc. 460 ft. over SW. slope.
24.25	Dirt road, 15 lks. wide, bears N. 58° W. and S. 58° E.
40.35	The E 1/16 sec. cor. of secs. 14 and 23.
From the N 1/16 sec. cor. of sec. 23 only.	
	S. 89° 40' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 23.
	Descend 30 ft. over SW. slope.
1.65	Spur, slopes S. 50° W.; desc. 30 ft. over NW. slope.
2.75	Ravine, drains S. 76° W.; desc. 60 ft. over NW. slope.
8.80	Spur, slopes S. 50° W.; desc. 155 ft. over W. slope.
16.75	Dirt road, 15 lks. wide, bears N. 25° W. and S. 25° E.
17.65	Deer Creek, 8 lks. wide, course N. 38° W.; asc. 75 ft. over NE. slope.
19.93	The NE 1/16 sec. cor. of sec. 23.
	Ascend 75 ft. over NE. slope.
29.00	Spur, slopes N.; desc. 75 ft. along N. slope.
36.40	Fence, bears N. and S.
36.95	Spur, slopes N. 31° W.; desc. 105 ft. over NW. slope.