

15813

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A black oak, 28 ins. diam., bears N. 59° E., 53 lks. dist., no marks visible on opened decayed blaze.

A decayed black oak stump, 40 ins. diam., bears S. 2° E., 157 lks. dist., no marks visible. (Record, 153 lks.)

A root hole, bears S. 81° W., 35 lks. dist., with a down black oak alongside, 30 ins. diam., no marks visible on opened decayed blaze.

and bearing trees mkd. by Mensch

A fir, 9 ins. diam., bears N. 51° E., 23 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears N. 62° W., 42 lks. dist., with healed blaze.

N. 87° 41' W., along the S. bdy. of sec. 34, T. 29 S., R. 7 W.

Ascend 40 ft. over SE. slope. *SEE*

2.85 Spur, slopes S. 10° W.; desc. 40 ft. over W. slope.

6.60 Ravine, drains S.; asc. 65 ft. over E. slope.

11.75 Spur, slopes S. 10° W.; desc. 230 ft. over W. slope.

21.60 Ravine, drains S. 40° W.; asc. 25 ft. over E. slope. *SEE*

25.00 Spur, slopes S. 15° W.; desc. 45 ft. over W. slope.

28.85 True point for the 1/4 sec. cor. of sec. 34 only, on the N. bdy. of T. 29 1/2 S., R. 7 W. *SEE*

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4 S 34
T 29 1/2 S R 7 W
1976

from which

A pine, 34 ins. diam., bears S. 72 1/2° E., 29 lks. dist., mkd. 1/4 S34 BT.

From this point, the original 1/4 sec. cor. of sec. 34, bears South, 0.084 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

1/4 S 34
1924
T 29 1/2

from which the original bearing trees

A madrone, 46 ins. diam., bears S. 3° E., 62 lks. dist., with healed blaze.

A madrone, 62 ins. diam., bears S. 54° W., 61 lks. dist., with healed blaze.

CORRECTIVE
DEPENDENT
RESURVEY
DF
12-23-81