

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

I add marks AM 1976

Descend 35 ft. over ~~S.~~ slope.

33.70 Ravine, drains S. 20° E.; asc. 85 ft. over SE. slope.

39.04 The $\frac{1}{2}$ sec. cor. of sec. 34 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

CORRECTIVE
DEPENDENT
RESURVEY of 12-23-81
S 34
1924

from which the original bearing trees

A madrone, 23 ins. diam., bears S. 81° W., 50 lks. dist., with scribe marks $\frac{1}{2}$ visible on opened blaze.

A madrone, 66 ins. diam., bears N. 15° W., 10 lks. dist., no marks visible. (Record, 8 lks.)

and bearing trees mkd. by Mensch

A fir, 9 ins. diam., bears N. 79° E., 29 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 15 ins. diam., bears N. 60° W., 3 lks. dist., with healed blaze.

Corner is located on top of a ridge, bears NE. and SW.

N. 89° 50' W., beginning new measurement.

Descend 445 ft. over NW. slope.

26.80 Creek, 5 lks. wide, course S. 40° W.; asc. 15 ft. over SW. slope.

28.10 Spur, slopes S. 20° W.; desc. 25 ft. over NW. slope.

29.11 The cor. of secs. 33 and 34 only, on the N. bdy. of T. 29 $\frac{1}{2}$ S., R. 7 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

S 33 | S 34
T 29 $\frac{1}{2}$ S | R 7 W
1924

from which the original bearing trees

A live oak, 22 ins. diam., bears S. 50° E., 55 lks. dist., with healed blaze.

A fir, 26 ins. diam., bears S. 71° W., 91 lks. dist., with healed blaze.

Descend 5 ft. over NW. slope.

30.00 Bottom of descent, slopes S.; asc. 170 ft. along S. slope.

38.09 The cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.