

15817

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree of no record

A fir, 62 ins. diam., bears S. 63° W., 24 lks.
dist., with healed blaze.

Ascend 20 ft. over NE. slope.

31.60 Spur, slopes NW.; desc. 130 ft. along N. slope.

38.45 The cor. of secs. 32 and 33 only, on the S. bdy. of the
Tp., monumented with an iron post, 2 ins. diam., firmly
set, projecting 8 ins. above ground, with brass cap mkd.

T 29 S	R 7 W
S 32	S 33
1924	

from which the remains of bearing trees mkd. by Mensch

A sawed fir stump, 17 ins. diam., bears
N. 72° W., 16 lks. dist., with fragmentary
scribe marks visible on opened blaze.

and bearing trees mkd. by James W. Byron, Deputy County
Surveyor, in 1962

A fir, 17 ins. diam., bears N. 34½° E.,
87 lks. dist., with healed blaze.

A fir, 21 ins. diam., bears N. 28° W.,
133 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, madrone, maple, chinquapin,
and oak; undergrowth, salal, hazel, Oregon grape, poison
oak, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 29 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford,
U. S. Deputy Surveyor, in 1854,
and the resurvey and survey by Fred Mensch,
Cadastral Engineer, in 1924)

From the SE. cor. of T. 29½ S., R. 7 W. and cor. of secs.
2, 3 and 35, on the S. bdy. of T. 29 S., R. 7 W., monu-
menting with an iron post, 3 ins. diam., firmly set,
projecting 15 ins. above ground, with brass cap mkd.

T 29½ S	T 29 S
R 7 W	
S 34	S 35
S 3	S 2
T 30 S R 7 W	
1924	

from which the remains of bearing trees mkd. by Mensch

A fir, 25 ins. diam., bears N. 54° E., 68 lks.
dist., with healed double blaze.

A root hole, bears S. 75° E., 42 lks. dist.,
with a down fir alongside, 15 ins. diam.,
with healed double blaze. (Record, 44 lks.)