

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A cedar snag, 9 ins. diam., bears S. 26° W.,
21 lks. dist., with scribe marks R7W visible
on open double blaze.

A fir, 38 ins. diam., bears N. 27½° W.,
86 lks. dist., with healed double blaze.
(Record, N. 29° W., 83 lks.)

and the remains of a bearing tree mkd. by the County
Surveyor, in 1962

A fir snag, 8 ins. diam., bears N. 34° E.,
38 lks. dist., with scribe marks S35 CS BT
visible on open double blaze.

and new bearing trees

A fir, 13 ins. diam., bears S. 54° E.,
69½ lks. dist., mkd. T30S R7W S2 BT.

A fir, 8 ins. diam., bears S. 36° W.,
39½ lks. dist., mkd. T30S R7W S3 BT.

N. 0° 46' W., along the W. bdy. of sec. 35, marking and
blazing the true line.

Ascend 270 ft. over SW. slope, through moderate timber
and light undergrowth.

8.05 Dirt road, 10 lks. wide, bears N. 65° W. and S. 40° E.,
in curve.

17.03 The NE. cor. of Tp. 29½ S., R. 7 W. and cor. of sec. 34½
only, T. 29 S., R. 7 W., on the W. bdy. of sec. 35,
hereinbefore described on the S. bdy. of T. 29 S., R. 7 W.

Ascend 145 ft. over S. slope.

24.35 Spur, slopes S. 30° W.; desc. 225 ft. over NW. slope.

33.55 Creek, 3 lks. wide, course N. 65° W.; asc. 45 ft. over
SW. slope.

36.20 Spur, slopes N. 60° W.; desc. 10 ft. over NW. slope.

37.04 The ¼ sec. cor. of secs. 34½ and 35, monumented with an
iron post, 1 in. diam., firmly set, projecting 9 ins.
above ground, with brass cap mkd.

¼
S 34½ | S 35
1924

from which the remains of the original bearing trees

A fir, 12 ins. diam., bears S. 55° E.,
17 lks. dist., with healed blaze.

and a bearing tree mkd. by the County Surveyor, in 1962

A fir, 40 ins. diam., bears S. 50½° W.,
21 lks. dist., with healed double blaze
and ¼ S34½ CS visible on bark.