

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 29 S R 7 W

$\frac{1}{4}$ $\frac{S 27}{S 34}$
 1974

from which a new bearing tree

A white fir, 21 ins. diam., bears N. $41\frac{1}{2}^\circ$ W.,
52 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

From this point, Cor. No. 1 of William Reynolds Mineral
Claim, bears N. $30^\circ 43'$ W., 1.25 chs. distance, deter-
mined at record bearing and distance from the original
bearing trees:

A red fir, 24 ins. diam., bears N. $12^\circ 20'$ E.,
 $36\frac{1}{2}$ lks. dist., with healed blaze.

A maple, 13 ins. diam., bears N. $87\frac{1}{2}^\circ$ E.,
44 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 29 S R 7 W

W R

1

$\frac{1}{4}$ $\frac{S 27}{S 34}$
 1974

from which a new bearing tree

A maple, 12 ins. diam., bears S. 65° W.,
11 lks. dist., mkd. WRC 1 BT.

N. $88^\circ 46'$ W., beginning new measurement.

Ascend 70 ft. over NE. slope.

4.65 Spur, slopes N. 30° W.; desc. 395 ft. over W. slope.

21.05 Creek, 3 lks. wide, course N. 30° W.; asc. 155 ft. over
NE. slope.

29.45 Spur, slopes N. 20° W.; desc. 165 ft. over NW. slope.

38.23 The cor. of secs. 27, 28, 33, and 34, monumented with an
iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

T 29 S R 7 W

$\frac{S 28}{S 33}$ | $\frac{S 27}{S 34}$

1957

from which the remains of the original bearing trees

A root hole, bears N. 32° E., 36 lks. dist.,
with a down madrone alongside, 30 ins. diam.,
no marks visible.

A madrone, 24 ins. diam., bears S. 46° E.,
23 lks. dist., with healed blaze. This tree
was rescribed by James W. Byron, Deputy County
Surveyor, in 1962, with scribe marks 29S R7W
S34 CS BT visible on partially healed blaze.