

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A broken fir stump, 10 ins. diam., bears N. 33° E.,  
11 lks. dist., with scribe marks TW visible on  
open blaze.

A fir, 21 ins. diam., bears S. 25° W., 28 lks.  
dist., with healed double blaze. This tree  
was rescribed by Byron.

A root hole, bears N. 71° W., 18 lks. dist., with  
a down fir alongside, 33 ins. diam., no marks  
visible.

and the remains of bearing trees mkd. by Byron

A fir, 16 ins. diam., bears N. 26° E., 25 lks.  
dist., with healed double blaze.

A root hole, bears S. 15° E., 54 lks. dist., with  
a down cedar alongside, 7 ins. diam., with scribe  
marks T30S R8W S27 CS BT visible on open double  
blaze.

and new bearing trees

A fir, 10 ins. diam., bears S. 82½° E., 56½ lks.  
dist., mkd. T30S R8W S27 BT.

A fir, 30 ins. diam., bears N. 36½° W., 46 lks.  
dist., mkd. T30S R8W S21 BT.

N. 0° 36' E., bet. secs. 21 and 22, marking and blazing  
the true line.

Ascend 60 ft. along W. slope, through heavy timber and  
moderate undergrowth.

5.85 Spur, slopes S. 55° W.; desc. 120 ft. over N. slope.

10.10 Creek, 3 lks. wide, course S. 85° W.; a c. 115 ft. over  
SW. slope.

21.20 Spur, slopes NW.; desc. 380 ft. over N. slope.

32.75 Creek, 2 lks. wide, course N. 55° W.; asc. 135 ft. over  
SW. slope.

39.26 The ¼ sec. cor. of secs. 21 and 22, determined at record  
bearing and distance from the remains of the original  
bearing trees:

A fir snag, 8 ins. diam., bears N. 36° W., 9 lks.  
dist., with scribe marks S BT visible on open  
blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 30 S R 8 W  
¼  
S 21 | S 22  
1975

FD OK  
9/19/6  
Debrout  
M125-51