

15827

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 20 ins. diam., bears S. 89° E., 39 lks.
dist., mkd. $\frac{1}{4}$ S22 BT.

A white fir, 20 ins. diam., bears N. 64° W., 67
lks. dist., mkd. $\frac{1}{4}$ S21 BT.

N. 0° 50' E., beginning new measurement.

Ascend 30 ft. over SW. slope, along E. edge of timber.

4.30 Spur, slopes W.; desc. 280 ft. over N. slope.

11.80 Creek, 4 lks. wide, course N. 60° W.; asc. 185 ft. over
SW. slope.

24.95 Spur, slopes N. 75° W.; desc. 65 ft. over NW. slope.

30.00 Creek, 4 lks. wide, course N. 85° W.; asc. 120 ft. over
SW. slope, changing to S.

39.41 The cor. of secs. 15, 16, 21, and 22, perpetuated and re-
corded by James W. Byron, County Surveyor, in 1965, monu-
mented with an iron post, 1 in. diam., firmly set, pro-
jecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 16 | S 15
S 21 | S 22
R 8 W
1965

from which the remains of the original bearing trees

A ponderosa pine, 40 ins. diam., bears N. 50° E.,
12 lks. dist., with healed blaze. (Record, 10
lks.)

A ponderosa pine snag, 11 ins. diam., bears
S. 72° E., 12 lks. dist., with scribe marks
T30S R BT visible on open blaze. (Record,
S. 60° E.)

A madrone, 13 ins. diam., bears S. 64° W., 31 lks.
dist., with scribe marks T S visible on opened
blaze.

A ponderosa pine, 25 ins. diam., bears N. 24° W.,
42 lks. dist., with healed blaze. (Record, 40
lks.)

and a bearing tree mkd. by Byron

A fir, 13 ins. diam., bears S. 44° E., 31½ lks.
dist., with healed double blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, pine, hemlock, yew, madrone, and
maple; undergrowth, salal, Oregon grape, poison oak,
hazel, huckleberry, and fern.

S. 88° 09' W., bet. secs. 16 and 21.