

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Descend 25 ft. along S. slope, through moderate timber and light undergrowth.

3.55 Creek, 2 lks. wide, course S. 20° E.; asc. 190 ft. along S. slope.

21.00 Spur, slopes SW.; desc. 200 ft. over W. slope.

40.09 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 8 W

$\frac{1}{4}$ S 16

S 21

1975

from which

A fir, 8 ins. diam., bears N. $71\frac{1}{2}^\circ$ E., 33 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

A fir, 15 ins. diam., bears S. $11\frac{1}{2}^\circ$ W., 30 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

Descend 185 ft. over W. slope.

59.05 Creek, 5 lks. wide, course S. 80° W.; asc. 30 ft. over SE. slope.

65.45 Top of ascent, slopes SW.; desc. 80 ft. over W. slope.

72.00 Creek, 3 lks. wide, course S. 10° W.; asc. 30 ft. over SE. slope.

78.50 Spur, slopes SW.; desc. 10 ft. over SW. slope.

80.18 The cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by James W. Byron, County Surveyor, in 1965, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S

S 17 | S 16

S 20 | S 21

R 8 W

1965

from which the remains of the original bearing trees

A madrone, 26 ins. diam., bears N. 14° E., 93 lks. dist., with scribe mark T visible on opened blaze.

A root hole, bears S. 37° E., 100 lks. dist., with a down ponderosa pine alongside 19 ins. diam., no marks visible on opened blaze.

and bearing trees mkd. by Byron

A fir, 15 ins. diam., bears N. 71° E., 21 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.