

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS  
39.34

Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 30 S R 8 W  
1/4 S 29  
S 32  
1975

from which

A fir, 22 ins. diam., bears N. 45 1/2° E., 35 lks. dist., mkd. 1/4 S29 BT.

A hemlock, 6 ins. diam., bears S. 45° W., 40 lks. dist., mkd. 1/4 S32 BT.

Ascend 225 ft. over E. slope.

50.60 Spur, slopes N. 25° E.; desc. 15 ft. over W. slope.

56.50 Ravine, drains N. 15° E.; asc. 80 ft. over E. slope.

59.01 Point for the W 1/16 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 29  
S 32  
1975

from which

A fir, 8 ins. diam., bears N. 7 1/2° E., 38 lks. dist., mkd. W 1/16 S29 BT.

A fir, 10 ins. diam., bears S. 10 1/2° E., 40 1/2 lks. dist., mkd. W 1/16 S32 BT.

Ascend 10 ft. over E. slope.

62.50 Spur, slopes N. 10° E.; desc. 30 ft. over NW. slope.

63.35 Ravine, drains N. 10° W.; asc. 85 ft. over broken E. slope.

75.70 Dirt road, 15 lks. wide, bears N. 5° E. and S. 5° W.

76.15 Dirt road, 15 lks. wide, bears NW. and SE.

78.68 The cor. of secs. 29, 30, 31, and 32, perpetuated and recorded by James W. Byron, County Surveyor, in 1965, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 30 S  
S 30 | S 29  
S 31 | S 32  
R 8 W  
1965

from which the remains of the original bearing trees