

Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 24 only, perpetuated and recorded by John H. Markham, Jr., RPE No. 2880, in 1951, monumented with the original basalt stone, 15 x 10 x 8 ins., lying on top of ground, mkd. $\frac{1}{4}$ on W. face, alongside of which is an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 40 ins. diam., bears N. 70° W.,
26 lks. dist., with axe marks visible.

and the remains of bearing trees mkd. by Strickler

A sawed fir stump, 27 ins. diam., bears S. 34 $\frac{1}{2}$ ° W.,
52 lks. dist., with axe marks visible.

and the remains of bearing trees mkd. by Markham

A sawed fir stump, 36 ins. diam., bears S. 66° E.,
59 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 29 S
R 3 W | R 2 W
 $\frac{1}{4}$ S 24 |
1976

from which new bearing trees

A fir, 7 ins. diam., bears S. 26° W., 134 lks.
dist., mkd. $\frac{1}{4}$ S24 BT.

A fir, 8 ins. diam., bears N. 63 $\frac{1}{2}$ ° W., 113 lks.
dist., mkd. $\frac{1}{4}$ S24 BT.

Insert iron pipe inside iron post and deposit
corner stone alongside iron post.

N. 1° 23' E., on the E. bdy. of sec. 24, marking and
blazing the true line.

Ascend over nearly level SE. slope, through moderate
timber and undergrowth.

0.24 The cor. of secs. 19 and 30 only, on the W. bdy. of
T. 29 S., R. 2 W., monumented with an iron post, 2 ins.
diam., firmly set, projecting 8 ins. above ground, with
brass cap mkd.

| T 29 S
| S 19
| S 30
| R 2 W
1917

from which the remains of the original bearing trees

A sawed fir stump, 26 ins. diam., bears N. 53 $\frac{1}{2}$ ° E.,
22 lks. dist., with healed blaze.

A root hole, bears S. 54° E., 32 lks. dist.