

Dependent Resurvey of a Portion of the East Boundary,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

## CHAINS

A fir, 11 ins. diam., bears S. 67° W., 29 lks.  
dist., with healed double blaze.

A fir, 12 ins. diam., bears N. 42° W., 29½ lks.  
dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 29 S		T 29 S
S 13		R 2 W
S 24		S 19
R 3 W		
		1976

from which a new bearing tree

A fir, 13 ins. diam., bears S. 68½° W., 105 lks.  
dist., mkd. T29S R3W S24 BT.

Insert iron pipe inside iron post, and deposit  
corner stone alongside iron post.

Land, mountainous.

Soil, clay loam.

Timber, fir, cedar, hemlock, madrone, and alder; under-  
growth, arrowwood, Oregon grape, salal, rhododendron,  
poison oak, and fern.

N. 1° 23' E., on the E. bdy. of sec. 13.

Descend 5 ft. over NW. slope, through heavy timber and  
moderate undergrowth.

0.20 The ¼ sec. cor. of sec. 19 only, T. 29 S., R. 2 W.,  
monumented with an iron post, 1 in. diam., firmly set,  
projecting 10 ins. above ground, with brass cap mkd.

¼		S 19
		1917

from which the original bearing tree

A fir, 45 ins. diam., bears N. 77° E., 93 lks.  
dist., with healed blaze.

and a new bearing tree

A fir, 15 ins. diam., bears S. 64½° E., 95 lks.  
dist., mkd. ¼ S19 BT.

Descend over gentle NW. slope.

0.25 Ravine, drains N. 70° W.; asc. 125 ft. over SW. slope.

9.70 Spur, slopes N. 80° W.; desc. 480 ft. over N. slope.

39.89 The ¼ sec. cor. of sec. 13 only, perpetuated and recorded  
by James W. Byron, Deputy County Surveyor, in 1962, de-  
termined from the remains of the original bearing trees:

A fir, 35 ins. diam., bears S. 28½° W., 101 lks.  
dist., with healed blaze.