

15839

Dependent Resurvey of a Portion of the East Boundary,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N.  $37^{\circ}$  W., 241 lks. dist., with  
a down fir alongside, 36 ins. diam., with healed  
blaze. (Record, N.  $34^{\circ}$  W.)

and bearing trees mkd. by Byron

A fir, 17 ins. diam., bears S.  $53^{\circ}$  W.,  $15\frac{1}{2}$  lks.  
dist., with healed double blaze.

A fir, 23 ins. diam., bears N.  $48\frac{3}{4}^{\circ}$  W.,  $22\frac{1}{2}$  lks.  
dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 29 S  
R 3 W | R 2 W  
 $\frac{1}{2}$  S 13 |  
1976

$1^{\circ} 23'$  E., beginning new measurement.

Descend 5 ft. over NW. slope, through moderate timber  
and light undergrowth.

0.16 The cor. of secs. 18 and 19, perpetuated and recorded by  
James W. Byron, Deputy County Surveyor, in 1962, monu-  
mented with an iron post,  $1\frac{1}{2}$  ins. diam., projecting 12  
ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
R 3 W | S 18 R 2 W  
| S 19 T 29 S  
1962

from which the original bearing trees

A fir, 53 ins. diam., bears N.  $\frac{1}{2}^{\circ}$  E., 253 lks.  
dist., with healed blaze. (Record, N.  $1\frac{1}{4}^{\circ}$  E.,  
263 lks.)

A fir, 47 ins. diam., bears S.  $29\frac{1}{2}^{\circ}$  E., 217 lks.  
dist., no marks visible on opened blaze.  
(Record, S.  $32^{\circ}$  E.)

and bearing trees mkd. by Byron

A fir, 10 ins. diam., bears N.  $84^{\circ}$  E.,  $35\frac{1}{2}$  lks.  
dist., with healed double blaze.

A fir, 14 ins. diam., bears S.  $15\frac{1}{2}^{\circ}$  E.,  $32\frac{1}{2}$  lks.  
dist., with healed double blaze.

Descend 135 ft. over NW. slope.

8.00 Ravine, drains N.  $25^{\circ}$  W.; desc. 60 ft. over broken NW.  
slope.

19.925 Point for the N  $1/16$  sec. cor. of sec. 13 only.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.