

15841

Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 1 and 12 only, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with the original basalt stone, 16 x 10 x 5 ins., mkd. with 5 notches on S. and 1 notch on N. edges, firmly set, projecting 6 ins. above ground, alongside of which is an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S		
R	S 1	R
3	S 12	2
W		W
1962		

From which the remains of the original bearing trees

A fir, 26 ins. diam., bears S. 72° E., 24 lks. dist., with fragmentary scribe marks visible on bark.

and the remains of bearing trees mkd. by Strickler

A sawed fir stump, 30 ins. diam., bears S. 20° W., 18 lks. dist., with healed blaze.

A fir, 34 ins. diam., bears N. 48° W., 50 lks. dist., with fragmentary scribe marks visible on bark.

and bearing trees mkd. by Byron

A cedar, 20 ins. diam., bears S. 81° W., 58 lks. dist., with scribe marks T29S R3W S12 CS BT visible on open blaze.

A cedar, 9 ins. diam., bears N. 22½° W., 44½ lks. dist., with scribe marks T29S R3W S1 CS BT visible on open blaze.

N. 0° 25' W., on the E. bdy. of sec. 1.

Ascend 5 ft. over SW. slope, through heavy timber and moderate undergrowth.

1.67

The ¼ sec. cor. of sec. 7 only, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

¼
S 7
1917

from which the original bearing trees

A cedar, 40 ins. diam., bears N. 71½° E., 47 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears S. 80° E., 30 lks. dist., with healed blaze.

Ascend 30 ft. over SW. slope.

14.60

Top of ascent, slopes W.; desc. 140 ft. over NW. slope.

25.20

Ravine, drains N. 80° W.; asc. 70 ft. over SW. slope.

25.85

Enter slide area, edge bears NE. and SW.

26.90

Top of ascent, slopes W.; desc. 170 ft. over NW. slope.