

15842

Dependent Resurvey of a Portion of the East Boundary,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS  
40.58

Point for the  $\frac{1}{4}$  sec. cor. of sec. 1 only, determined by the method of broken boundaries, falls on a sandstone boulder, 4 x 4 x 4 ft. above ground; there is no remaining evidence of the original corner.

Set a brass tablet,  $3\frac{1}{4}$  ins. diam.,  $3\frac{1}{2}$  ins. stem, in drill hole in boulder, with top mkd.

T 29 S
R 3 W   R 2 W
$\frac{1}{4}$ S 1
1976

from which a bearing object

A sandstone boulder, 30 x 20 x 15 ft. above ground, bears N.  $42^\circ$  W., 73 lks. dist., mkd. X BO on SE. face.

No suitable trees available within limits.

N.  $4^\circ 28'$  E., beginning new measurement.

Descend 25 ft. over N. slope.

1.27 Point for the cor. of secs. 6 and 7 only, T. 29 S., R. 2 W., determined by the method of broken boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T 29 S   T 29 S
R 3 W   S 6
S 1   S 7
S 1   R 2 W
1976

from which

A madrone, 8 ins. diam., bears N.  $80^\circ$  E., 30 lks. dist., mkd. T29S R2W S6 BT.

A sandstone boulder, 15 x 10 x 6 ft. above ground, bears S.  $79\frac{1}{2}^\circ$  E.,  $48\frac{1}{2}$  lks. dist., mkd. X BO on W. face.

Descend 290 ft. over NW. slope.

26.45 Leave slide area, enter heavy timber and medium undergrowth.

38.65 The cor. of Tps. 29 S., Rs. 2 and 3 W., established by Byars, in 1881, changed to a corner of minimum control by Gibb, in 1910, and rehabilitated by Strickler, in 1917, monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 28 S R 3 W
S 36
S 1   S 6
R 3 W   R 2 W
T 29 S
1917

from which the remains of the original bearing trees